



Miami Heat Pump

20233 N.E. 15th Court Miami Fl, 33179

Phone (866)407-8535 * Fax (866)406-6603

Website: www.miamihp.com * Email: customerservice@miamihp.com

UNIT SPECIFICATION DATA SHEET

UNIT MODEL

HPHWW060 SS -

Water To Water Heat Pump

FEATURE INFORMATION

CABINET - Stainless Steel
 COND. COIL - Coaxial - Cupronickel
 COND FANS - N/A
 EVAP. COIL - Coaxial Tube in Tube Cupronickel
 COMPRESSOR- Copeland Scroll
 REF. CIRCUITS - 1 Independent Circuit
 SAFETY - High/Low Press. Switches, Overload Protection, Anti-Freeze Protection, Time Delay, Lock-out Relay, Phase Monitor and Voltage Protection
 & CONTROL 24 Volt,

UNIT PERFORMANCE

GROUND LOOP

COOLING		HEATING	
Indoor Side	53.6 ° F	Indoor Side	104 ° F
Geothermal side	77 ° F	Geothermal Side	32 ° F
BTUH	EER	BTUH	COP
55,300	16	47,900	3.0

GROUND WATER LOOP

COOLING		HEATING	
Indoor Side	53.6 ° F	Indoor Side	104 ° F
Geothermal side	59 ° F	Geothermal Side	50 ° F
BTUH	EER	BTUH	COP
56,400	19.8	54,900	3.8

MIN AMP. / MAX FUSE - AMPS. 38.6 / 50
 VOLTAGE RATING / PHASE / HERTZ - 208-230/1/60
 DIMENSION W" X L" X H" - 24" x 26" x 26"
 WEIGHT - NET - 220

1. UNIT IS SUBJECT TO CHANGE WITHOUT NOTICE
2. UNIT IF AVAILABLE IN DIFFERENT CONFIGURATIONS AND VOLTAGE RATINGS

