



Miami Heat Pump
 20233 N.E. 15th Court Miami Fl, 33179
 Phone (866) 407-8535 - Fax (866)406-6603
 Website: www.miamihp.com - Email: customerservice@miamihp.com

Specification Capacity Data Sheet

HPX024

Water Loop				Ground Water				Ground Loop			
Cooling		Heating		Cooling		Heating		Cooling		Heating	
Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP
25,500	17.0	27,500	5.0	27,500	27.6	20,500	4.2	25,500	19.7	16,500	3.6

Performance at	
800	CFM
6.0	GPM

Cooling							
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Sensible Capacity (MBtuH)	SHF	Power Input (kW)	Heating of Reject (MBtuH)	EER
50	70 db 61 wb	31.27	10.41	0.33	1.03	34.16	36.10
59		30.08	9.98	0.33	1.18	33.49	29.60
70		28.63	9.38	0.33	1.37	32.68	23.70
86		26.39	8.61	0.33	1.67	31.45	17.60
100		24.37	0.00	0.00	1.97	30.42	13.50
50	75 db 63 wb	27.74	19.77	0.71	1.04	30.65	31.80
59		26.82	19.56	0.73	1.19	30.23	26.30
70		25.41	18.79	0.74	1.36	29.43	21.20
86		23.45	17.93	0.76	1.65	28.44	15.80
100		21.70	17.05	0.79	1.95	27.71	12.20
50	80.6 db 66.2 wb	29.35	21.63	0.74	1.03	32.23	34.00
59		27.50	20.62	0.75	1.17	30.86	27.40
70		26.87	20.56	0.77	1.36	30.87	22.50
86		25.50	20.11	0.79	1.67	30.55	17.00
100		22.93	18.87	0.82	1.95	28.95	12.80
50	85 db 71 wb	31.76	21.15	0.67	1.07	34.78	35.00
59		30.56	20.58	0.67	1.16	33.89	30.70
70		29.06	19.99	0.69	1.35	33.02	24.60
86		26.79	19.19	0.72	1.64	31.75	18.20
100		24.78	18.35	0.74	1.94	30.75	14.00

Heating					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
50	60	21.85	1.52	17.22	4.7
60		24.52	1.56	19.77	5.2
68		26.68	1.58	21.86	5.5
80		30.25	1.64	25.23	6.0
100		20.50	1.60	15.62	4.2
50	68	24.08	1.70	18.87	4.6
68		27.50	1.78	22.00	5.0
80		29.78	1.78	24.28	5.4
100		21.13	1.89	15.24	3.6
50	80	23.62	1.92	17.65	4.0
68		25.80	1.95	19.71	4.2
80		29.28	2.04	22.90	4.6

Low Temp Heating (with Antifreeze by ARI-ISO13256-1)					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
25	60	15.19	1.38	11.07	3.7
32		16.73	1.39	12.54	4.0
40		18.59	1.41	14.36	4.4
25	68	14.97	1.50	10.45	3.3
32		16.50	1.51	11.92	3.6
40		18.34	1.53	13.70	3.9
25	80	14.74	1.70	9.50	2.8
32		16.25	1.73	10.93	3.1
40		18.05	1.74	12.68	3.4

Fluid Press. Drop		
Fluid Flow (GPM)	Pressure Drop	
	(FOH)	(PSIG)
3.0	1.4	0.6
4.0	2.6	1.1
5.3	4.5	1.9
6.0	5.8	2.5
7.5	9.0	3.9



	Weight (lbs)		Dimension		
	Unit	Shipping	Length	Width	Height
Vertical	210	230	21.50	21.50	39.00
Horizontal	210	230	33.50	21.50	20.75

Electrical Specification					
Electrical Characteristic	Electric. Symbol	Compressor		Min Circuit	Max Fuse Size
		RLA	LRA		
230/1/60		12.8	60	19	30
230/3/60	C	7.8	55	13	20
460/3/60	D	3.9	22.4	6	15
265/1/60	B	10.9	58	16	25

Units are subject to change without notice please contact us for up-to-date values.



Miami Heat Pump
 20233 N.E. 15th Court Miami FL, 33179
 Phone (866) 407-8535 - Fax (866)406-6603
 Website: www.miamihp.com - Email: customerservice@miamihp.com

Specification Capacity Data Sheet

HPX031

Water Loop				Ground Water				Ground Loop				Performance at	
Cooling		Heating		Cooling		Heating		Cooling		Heating		1,000	CFM
Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	7.5	GPM
31,000	16.0	36,000	4.8	39,000	26.0	27,000	4.1	31,800	17.6	20,000	3.6		

Cooling							
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Sensible Capacity (MBtuH)	SHF	Power Input (kW)	Heating of Reject (MBtuH)	EER
50	70 db 61 wb	36.08	23.88	0.66	1.65	40.72	26.5
59		34.34	23.07	0.67	1.79	39.45	22.9
70		32.13	22.05	0.69	1.97	37.86	19.1
86		28.82	20.58	0.71	2.21	35.38	15.0
100		25.81	19.21	0.74	2.42	33.10	12.1
50	75 db 63 wb	37.52	26.98	0.72	1.64	42.13	27.8
59		35.71	25.66	0.72	1.78	40.81	23.9
70		33.43	24.60	0.74	1.97	39.17	19.9
86		30.03	22.97	0.77	2.23	36.65	15.5
100		26.90	21.58	0.80	2.44	34.26	12.5
50	80.6 db 66.2 wb	39.86	28.84	0.72	1.62	44.41	29.9
59		39.00	28.76	0.74	1.79	44.12	26.0
70		35.52	26.88	0.76	1.96	41.25	21.2
86		31.00	24.65	0.80	2.22	37.61	16.0
100		28.63	23.93	0.84	2.33	35.59	14.0
50	85 db 71 wb	43.52	28.93	0.66	1.57	47.90	33.9
59		41.39	28.08	0.68	1.81	46.59	27.2
70		38.78	26.98	0.70	1.98	44.55	22.9
86		34.87	24.82	0.71	2.26	41.60	17.7
100		31.40	23.50	0.75	2.37	38.50	15.1

Heating					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
50	60	28.69	2.15	22.32	4.5
60		33.00	2.26	26.26	5.9
68		36.52	2.33	29.56	5.2
80		41.69	2.38	34.56	5.8
50	68	27.00	2.22	20.41	4.1
60		31.73	2.37	24.62	4.5
68		36.00	2.49	28.50	4.8
80		40.45	2.54	32.76	5.3
50	80	25.87	2.38	18.72	3.6
60		29.90	2.53	22.25	3.9
68		33.38	2.64	25.36	4.2
80		38.55	2.77	30.08	4.6

Low Temp Heating (with Antifreeze by ARI-ISO13256-1)					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
25	60	18.28	1.80	13.13	3.6
32		20.93	1.90	15.44	3.8
40		24.15	2.00	18.29	4.1
25	68	17.40	1.85	12.06	3.3
32		20.00	1.96	14.29	3.5
40		23.14	2.09	17.01	3.8
25	80	16.04	1.93	10.45	2.9
32		18.57	2.05	12.55	3.1
40		21.59	2.19	15.11	3.3

Fluid Press. Drop		
Fluid Flow (GPM)	Pressure Drop (FOH) (PSIG)	
3.8	2.1	0.9
5.0	3.8	1.7
6.6	6.6	2.9
7.5	8.5	3.7
9.4	13.3	5.8



	Weight (lbs)		Dimension		
	Unit	Shipping	Length	Width	Height
Vertical	210	230	21.50	21.50	39.00
Horizontal	210	230	33.50	21.50	20.75

Electrical Specification					
Electrical Characteristic	Electric. Symbol	Compressor		Min Circuit	Max Fuse Size
		RLA	LRA		
230/1/60		14.7	72.5	24	35
230/3/60	C	10.4	63	19	25
460/3/60	D	4.5	31	9	15
265/1/60	B	12.5	61	16	25

Units are subject to change without notice please contact us for up-to-date values.



Miami Heat Pump
 20233 N.E. 15th Court Miami FL, 33179
 Phone (866)407-8535 - Fax (866)406-6603
 Website: www.miamihp.com - Email: customerservice@miamihp.com

Specification Capacity Data Sheet

HPX036

Water Loop				Ground Water				Ground Loop			
Cooling		Heating		Cooling		Heating		Cooling		Heating	
Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP
36,00	16.0	40,000	4.8	40,000	23.5	32,000	4.2	36,500	17.9	26,000	3.6

Performance at	
1,200	CFM
9.0	GPM

Cooling							
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Sensible Capacity (MBtuH)	SHF	Power Input (kW)	Heating of Reject (MBtuH)	EER
50	70 db 61 wb	38.47	25.24	0.66	1.79	43.55	25.90
59		37.05	24.57	0.66	1.97	42.74	22.20
70		35.28	23.77	0.67	2.20	41.73	18.60
86		32.62	22.43	0.69	2.57	40.33	14.40
100		30.19	21.29	0.71	2.95	39.22	11.40
50	75 db 63 wb	39.80	28.37	0.71	1.80	44.89	26.70
59		38.34	27.72	0.72	1.98	44.05	22.90
70		36.54	26.82	0.73	2.21	43.03	19.20
86		33.79	25.53	0.76	2.57	41.52	14.80
100		31.25	24.49	0.78	2.95	40.28	11.80
50	80.6 db 66.2 wb	41.97	30.84	0.73	1.81	47.10	27.90
59		40.00	29.74	0.74	2.01	45.81	23.50
70		38.57	29.23	0.76	2.22	45.09	20.20
86		36.00	28.39	0.79	2.56	4368.00	16.00
100		33.02	27.01	0.82	2.95	42.06	12.58
50	85 db 71 wb	45.35	30.16	0.66	1.82	50.53	29.90
59		43.75	29.39	0.67	2.00	49.54	25.80
70		41.66	28.55	0.69	2.24	48.26	21.60
86		38.51	27.46	0.71	2.61	46.38	16.70
100		35.88	26.44	0.74	2.97	44.98	13.50

22.2

Heating					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
50	60	32.69	2.42	25.49	4.5
60		36.92	2.47	29.53	5.0
68		40.40	2.51	32.87	5.4
80		45.63	2.58	37.86	5.9
100		50.00	2.64	42.00	6.4
50	68	32.00	2.54	24.38	4.2
60		36.31	2.64	28.35	4.6
68		40.00	2.75	31.67	4.8
80		44.85	2.76	36.48	5.4
100		50.00	2.93	41.52	6.0
50	80	31.78	2.93	22.84	3.6
60		36.65	2.96	26.61	3.9
68		38.71	2.99	29.54	4.2
80		43.82	3.08	34.36	4.6
100		50.00	3.15	36.00	4.8

Low Temp Heating (with Antifreeze by ARI-ISO13256-1)					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
25	60	23.87	2.21	17.38	3.7
32		26.34	2.25	19.71	4.0
40		29.25	2.30	22.45	4.3
25	68	23.62	2.37	16.56	3.3
32		26.00	2.42	18.78	3.6
40		28.89	2.48	21.46	3.9
25	80	20.84	2.65	12.83	2.6
32		24.42	2.73	16.13	2.9
40		28.67	2.85	19.98	3.3

Fluid Press. Drop		
Fluid Flow (GPM)	Pressure Drop (FOH) (PSIG)	
4.5	4.0	1.8
6.0	7.2	3.1
7.9	12.5	5.4
9.0	16.1	7.0
11.3	25.2	10.9



	Weight (lbs)		Dimension		
	Unit	Shipping	Length	Width	Height
Vertical	210	240	21.50	21.50	39.00
Horizontal	210	235	33.50	21.50	20.75

Electrical Specification					
Electrical Characteristic	Electric. Symbol	Compressor		Min Circuit	Max Fuse Size
		RLA	LRA		
230/1/60		16.7	79	27	40
230/3/60	C	10.4	73	19	25
460/3/60	D	5.7	38	10	15
265/1/60	B	3.8	36.5	7	15

Units are subject to change without notice please contact us for up-to-date values.



Miami Heat Pump
 20233 N.E. 15th Court Miami FL, 33179
 Phone (866) 407-8535 - Fax (866)406-6603
 Website: www.miamihp.com - Email: customerservice@miamihp.com

Specification Capacity Data Sheet

HPX041

Water Loop				Ground Water				Ground Loop				Performance at	
Cooling		Heating		Cooling		Heating		Cooling		Heating		1,400	CFM
Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	10.5	GPM
41,000	16.0	47,000	4.8	47,000	21.4	37,500	4.1	44,000	17.2	26,500	3.6		

Cooling							
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Sensible Capacity (MBtuH)	SHF	Power Input (kW)	Heating of Reject (MBtuH)	EER
50	70 db 61 wb	45.71	30.67	0.67	2.37	52.42	23.2
59		43.59	29.72	0.68	2.52	50.93	20.5
70		40.91	28.48	0.70	2.72	48.82	17.6
86		36.85	26.55	0.72	3.03	45.82	14.0
100		33.01	24.79	0.75	3.29	42.89	11.4
50	75 db 63 wb	47.38	34.81	0.73	2.36	54.07	24.1
59		45.18	33.81	0.75	2.52	52.41	21.3
70		42.40	32.58	0.77	2.72	50.32	18.2
86		38.18	30.60	0.80	3.04	47.18	14.5
100		34.22	28.93	0.85	3.31	44.16	11.7
50	80.6 db 66.2 wb	36.22	32.22	0.89	3.36	46.31	12.3
59		47.00	36.48	0.78	2.60	54.49	21.4
70		44.84	35.85	0.80	2.73	52.77	19.3
86		41.00	0.00	0.00	2.96	49.74	16.0
100		50.12	38.06	0.76	2.35	56.77	25.7
50	85 db 71 wb	54.17	37.28	0.69	2.32	60.72	28.2
59		51.73	36.30	0.70	2.49	58.86	24.7
70		48.52	35.12	0.72	2.71	56.41	21.0
86		43.57	33.18	0.76	3.06	52.65	16.4
100		39.01	31.32	0.80	3.38	49.17	13.1

Heating					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
50	60	38.86	2.96	30.14	4.5
60		44.52	3.08	35.38	4.9
68		48.98	3.14	39.64	5.2
80		55.39	3.17	45.94	5.9
50	68	37.50	3.08	28.35	4.1
60		42.90	3.21	33.30	4.5
68		47.00	3.27	37.21	4.8
80		53.52	3.35	43.45	5.3
50	80	0.00	0.40	0.00	3.6
60		40.61	3.41	30.33	4.0
68		44.83	3.52	34.19	4.2
80		0.00	0.40	0.00	4.6

Low Temp Heating (with Antifreeze by ARI-ISO13256-1)					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
25	60	24.30	2.43	17.40	3.5
32		27.75	2.54	20.47	3.8
40		31.58	2.66	23.88	4.1
25	68	22.97	2.49	15.85	3.2
32		26.50	2.62	18.93	3.5
40		30.32	2.75	22.28	3.8
25	80	21.49	2.58	14.06	2.9
32		24.13	2.71	16.27	3.1
40		28.34	2.89	19.86	3.3

Fluid Press. Drop		
Fluid Flow (GPM)	Pressure Drop	
	(FOH)	(PSIG)
5.3	5.1	2.2
7.0	9.1	4.0
9.2	15.7	6.8
10.5	20.2	8.8
13.1	31.6	13.8



	Weight (lbs)		Dimension		
	Unit	Shipping	Length	Width	Height
Vertical	220	240	21.50	21.50	39.00
Horizontal	215	235	33.50	21.50	20.75

Electrical Specification					
Electrical Characteristic	Electric. Symbol	Compressor		Min Circuit	Max Fuse Size
		RLA	LRA		
230/1/60		17.9	112	28	45
230/3/60	C	13.2	6	23	35
460/3/60	D	5.9	37	10	15

Units are subject to change without notice please contact us for up-to-date values.



Miami Heat Pump
 20233 N.E. 15th Court Miami FL, 33179
 Phone (866)407-8535 - Fax (866)406-6603
 Website: www.miamihp.com - Email: customerservice@miamihp.com

Specification Capacity Data Sheet

HPX048

Water Loop				Ground Water				Ground Loop			
Cooling		Heating		Cooling		Heating		Cooling		Heating	
Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP
51,000	18.0	58,000	5.0	57,000	27.0	50,000	4.3	53,000	20	39,000	3.6

Performance at	
1,600	CFM
12.0	GPM

Cooling							
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Sensible Capacity (MBtuH)	SHF	Power Input (kW)	Heating of Reject (MBtuH)	EER
50	70 db 61 wb	53.61	35.38	0.66	2.25	59.69	30.1
59		51.60	34.40	0.67	2.53	58.61	25.1
70		49.05	33.17	0.68	2.83	57.09	20.8
86		45.65	32.01	0.70	3.34	55.44	15.9
100		41.80	29.62	0.71	3.82	53.22	12.5
50	75 db 63 wb	55.50	39.89	0.72	2.24	61.55	31.3
59		53.43	38.87	0.73	2.52	60.42	26.1
70		51.23	38.28	0.75	2.85	59.34	21.5
86		46.91	35.76	0.76	3.34	56.72	16.3
100		44.88	35.16	0.78	3.90	56.58	13.1
50	80.6 db 66.2 wb	59.08	43.83	0.74	2.22	65.05	33.7
59		57.00	43.06	0.76	2.58	64.20	27.0
70		54.16	42.05	0.78	2.84	62.25	22.8
86		51.00	40.09	0.79	3.30	60.67	18.0
100		46.30	38.74	0.84	3.82	57.74	13.8
50	85 db 71 wb	63.80	42.84	0.67	2.18	69.64	37.3
59		61.39	42.12	0.69	2.48	68.23	30.6
70		58.37	40.96	0.70	2.83	66.42	24.7
86		54.01	39.46	0.73	3.34	63.81	18.8
100		50.07	37.88	0.76	3.82	61.51	14.9

Heating					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
50	60	49.68	3.57	39.12	4.7
60		55.83	3.64	45.02	5.2
68		60.84	3.70	49.82	5.5
80		68.28	3.77	57.03	6.1
100		75.00	3.88	63.87	6.6
50	68	54.70	3.89	43.05	4.7
60		58.00	3.87	46.40	5.0
68		66.85	4.04	54.66	5.5
80		74.72	4.21	63.96	6.1
100		81.13	4.29	71.08	6.6
50	80	57.74	4.37	44.42	4.3
60		64.87	4.50	51.13	4.7
68					
80					
100					

Low Temp Heating (with Antifreeze by ARI-ISO13256-1)					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
25	60	36.08	3.32	26.35	3.7
32		39.61	3.39	29.65	4.0
40		43.73	3.45	33.54	4.3
25	68	35.58	3.57	25.02	3.4
32		39.00	3.65	28.17	3.6
40		42.95	3.67	32.02	3.9
25	80	34.86	3.93	23.05	3.0
32		38.16	3.98	26.18	3.2
40		42.25	4.06	29.99	3.4

Fluid Press. Drop		
Fluid Flow (GPM)	Pressure Drop	
	(FOH)	(PSIG)
6.0	3.3	1.4
8.0	5.9	2.6
10.6	10.2	4.4
12.0	13.1	5.7
15.0	20.5	8.9



	Weight (lbs)		Dimension		
	Unit	Shipping	Length	Width	Height
Vertical	320	340	26.00	24.00	43.00
Horizontal	330	350	45.50	26.00	21.00

Electrical Specification					
Electrical Characteristic	Electric. Symbol	Compressor		Min Circuit	Max Fuse Size
		RLA	LRA		
230/1/60		24.3	117	36	50
230/3/60	C	13.7	83.1	23	35
460/3/60	D	6.1	41	11	15

Units are subject to change without notice please contact us for up-to-date values.



Miami Heat Pump
 20233 N.E. 15th Court Miami FL, 33179
 Phone (866)407-8535 - Fax (866)406-6603
 Website: www.miamihp.com - Email: customerservice@miamihp.com

Specification Performance Data Sheet

HPX060

Water Loop				Ground Water				Ground Loop			
Cooling		Heating		Cooling		Heating		Cooling		Heating	
Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP	Capacity	EER	Capacity	COP
60,000	16.0	70,000	4.5	68,000	22.0	58,000	4.1	63,000	17.2	45,000	3.6

Performance at	
1,900	CFM
15.0	GPM

Cooling							
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Sensible Capacity (MBtuH)	SHF	Power Input (kW)	Heating of Reject (MBtuH)	EER
50	70 db 61 wb	64.55	42.23	0.65	3.17	73.68	24.1
59		62.22	41.18	0.66	3.43	72.25	21.2
70		59.28	39.78	0.67	3.79	70.54	18.0
86		54.84	37.70	0.69	4.40	68.18	14.0
100		50.87	35.95	0.71	4.97	66.14	11.4
50	75 db 63 wb	66.82	47.60	0.71	3.17	75.96	25.0
59		64.42	46.48	0.72	3.44	74.48	21.8
70		61.41	45.02	0.73	3.80	72.71	18.5
86		56.74	43.42	0.77	4.38	70.00	14.6
100		52.66	41.43	0.79	4.97	67.95	11.7
50	80.6 db 66.2 wb	70.59	52.08	0.74	3.19	79.79	26.2
59		68.00	50.92	0.75	3.58	78.55	22.0
70		64.77	49.65	0.77	3.81	76.09	19.5
86		60.00	47.41	0.79	4.24	72.80	16.0
100		55.49	45.97	0.83	4.98	70.83	12.3
50	85 db 71 wb	76.35	50.74	0.66	3.22	85.66	28.0
59		73.61	49.56	0.67	3.49	83.83	24.6
70		70.11	48.63	0.69	3.84	81.54	20.9
86		64.94	46.19	0.71	4.42	78.36	16.5
100		60.10	44.68	0.74	5.04	75.63	13.2

Heating					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
50	60	58.05	4.39	44.74	4.4
60		65.48	4.53	51.70	4.8
68		71.67	4.66	57.46	5.0
80		81.88	4.89	66.87	5.5
100		100.00	5.00	75.00	5.0
50	68	58.00	4.64	43.85	4.1
60		64.01	4.82	49.24	4.3
68		70.00	5.05	54.44	4.5
80		80.57	5.23	64.39	5.0
50	80	55.68	5.19	39.62	3.5
60		62.84	5.37	46.20	3.8
68		69.02	5.53	51.82	4.0
80		78.65	5.80	60.53	4.3

Low Temp Heating (with Antifreeze by ARI-ISO13256-1)					
Entering Fluid Temp (°F)	Entering Air Temp (°F)	Total Capacity (MBtuH)	Power Input (kW)	Heating of Abs. (MBtuH)	COP
25	60	41.94	3.92	30.24	3.6
32		45.83	3.98	33.91	3.8
40		50.74	4.07	38.51	4.2
25	68	41.34	4.18	28.73	3.3
32		45.00	4.26	32.14	3.5
40		49.69	4.36	36.50	3.8
25	80	40.41	4.65	26.23	2.8
32		44.14	4.74	29.63	3.0
40		48.47	4.83	33.65	3.3

Fluid Press. Drop		
Fluid Flow (GPM)	Pressure Drop	
	(FOH)	(PSIG)
7.5	4.6	2.0
10.1	8.3	3.6
13.2	14.2	6.2
15.0	18.4	8.0
18.8	28.8	12.5



	Weight (lbs)		Dimension		
	Unit	Shipping	Length	Width	Height
Vertical	320	340	26.00	24.00	43.00
Horizontal	340	360	45.50	26.00	21.00

Electrical Specification					
Electrical Characteristic	Electric. Symbol	Compressor		Min Circuit	Max Fuse Size
		RLA	LRA		
230/1/60		26.4	134	39	60
230/3/60	C	16	110	26	40
460/3/60	D	7.8	52	13	20
575/1/60	E	5.7	38.9	10	15

Units are subject to change without notice please contact us for up-to-date values.