



# Miami Heat Pump

20233 N.E. 15th Court Miami Fl, 33179  
Toll Free: 866-407-8535 - Fax (866)407-8535  
Website: www.miamihp.com - Email: customerservice@miamihp.com

## UNIT SPECIFICATION DATA SHEET

### UNIT MODEL

**HPX 060H - SS**  
**Water Source Heat Pump**  
**AHRI Certified # 4547874**



EnergyStar # 1105381

### FEATURE INFORMATION

CABINET -	Stainless Steel, Insulated Evaporator Section, Access Panels
DRAIN PAN -	Stainless Steel, Insulated.
SAFETY -	High/Low Press. Switches, Condensate Over-Flow Switch, Overload Protection Anti Short Cycle Relay/s, Lock-out Relay/s
BLOWER/S -	Centrifugal Galvanized Wheel/s, BLDC Motor
REF. CIRCUITS -	Thermal Expansion Valve 1 circuit
COND. COIL -	Coaxial - Cupronickel Heat Exchanger - & Steel Jacket,
EVAP. COIL -	Copper Tubes, Aluminum Fins
REFRIGERANT-	R-410A



### UNIT PERFORMANCE

EVAP COOLING CAPACITY - BTU/HR	WLHP 60,000	GWHP 68,000	GLHP 63,000
HEATING CAP. - BTU/HR (HEAT PUMP MODE)	WLHP 70,000	GWHP 58,000	GLHP 45,000
FACE VELOCITY - FPM	334		
COIL ENTERING AIR TEMP. DB/WB - °F	80.6° / 66.2°		

### BLOWER/S

AIR VOLUME - CFM	1900		
ESP - IN H2O	0.6		
BLOWER SIZE & QTY	10" x 10" / 1		
FAN MOTOR - HP & QTY	3/4 / 1	FLA(EA)=	6.0 A

### CONDENSER/S

WATER FLOW - GPM	15.0			
ENTERING WATER TEMP. °F	WLHP 86.0°	GWHP 59.0°	GLHP 77.0°	
WATER PRESS. DROP - FT H2O	4.5			

### COMPRESSOR

NO. OF CIRCUIT / CAPACITY STEPS	1 / 1			
TYPE & QTY	Scroll / 1	RLA(EA)=	26.4 A	LRA(EA)= 134.0 A

### GENERAL

VOLTAGE RATING / PHASE / HERTZ	230/1/60			
E.E.R.	WLHP 16.0	GWHP 22.0	GLHP 17.2	
C.O.P (HEAT-PUMP ONLY)	WLHP 4.5	GWHP 4.1	GLHP 3.6	
MIN AMP. / MAX FUSE - AMPS.	39 / 60			
DIMENSION W" X L" X H"	26" x 45.50" x 20.75"			
WEIGHT - NET - LBS.	330			
WATER CONNECTION SIZE	1			
DRAIN CONNECTION SIZE	3/4			

### NOTES:

1. UNIT ARE SUBJECT TO CHANGE WITHOUT NOTICE
2. UNIT IF AVAILABLE IN DIFFERENT CONFIGURATIONS AND VOLTAGE RATINGS