



Miami Heat Pump
20233 N.E. 15th Court Miami FL, 33179
Toll Free: 866-407-8535 - Fax (866)406-6603
Website: www.miamihp.com - Email: customerservice@miamihp.com

UNIT SPECIFICATION DATA SHEET

UNIT MODEL
HPX 024H - SS
Water Source Heat Pump
AHRI Certified Reference # 4547869



EnergyStar # 1105381

FEATURE INFORMATION

CABINET - Stainless Steel, Insulated Evaporator Section, Access Panels
DRAIN PAN - Stainless Steel, Insulated.
SAFETY - High/Low Press. Switches, Condensate Over-Flow Switch, Overload Protection
Anti Short Cycle Relay/s, Lock-out Relay/s
BLOWER/S - Centrifugal Galvanized Wheel/s, X13 ECM Motor
REF. CIRCUITS - Thermal Expansion Valve 1 circuit
COND. COIL - Coaxial - Cupronickel Haet Exchanger - & Steel Jacket,
EVAP. COIL - Copper Tubes, Aluminum Fins
REFRIGERANT- R454B



UNIT PERFORMANCE

EVAP COOLING CAPACITY - BTU/HR	WLHP 25,500	GWHP 27,500	GLHP 25,500
HEATING CAP. - BTU/HR (HEAT PUMP MODE)	WLHP 27,500	GWHP 20,500	GLHP 16,500
FACE VELOCITY - FPM	222		
COIL ENTERING AIR TEMP. DB/WB - °F	80.6° / 66.2°		

BLOWER/S

AIR VOLUME - CFM	800		
ESP - IN H2O	0.6		
BLOWER SIZE & QTY	10" x 7" / 1		
FAN MOTOR - HP & QTY	1/3 / 1	FLA(EA)= 2.8 A	

CONDENSER/S

WATER FLOW - GPM	6.0		
ENTERING WATER TEMP. °F	WLHP 86.0°	GWHP 59.0°	GLHP 77.0°
WATER PRESS. DROP - FT H2O	11.4		

COMPRESSOR

NO. OF CIRCUIT / CAPACITY STEPS	1 / 1		
TYPE & QTY	Scroll / 1	RLA(EA)= 12.8 A	LRA(EA)= 60.0 A

GENERAL

VOLTAGE RATING / PHASE / HERTZ	230/1/60		
E.E.R.	WLHP 17.0	GWHP 27.6	GLHP 19.7
C.O.P (HEAT-PUMP ONLY)	WLHP 5.0	GWHP 4.2	GLHP 3.6
MIN AMP. / MAX FUSE - AMPS.	19 / 30		
DIMENSION W" X L" X H"	21.50" x 33.50" x 20.75"		
WEIGHT - NET - LBS.	210		
WATER CONNECTION SIZE	3/4		
DRAIN CONNECTION SIZE	3/4		

NOTES:
1. UNIT ARE SUBJECT TO CHANGE WITHOUT NOTICE
2. UNIT IF AVAILABLE IN DIFFERENT CONFIGURATIONS AND VOLTAGE RATINGS